MEYER SUB-RENTAL DIVISION



MEYER Sub-Rental Division

MEYER's rental facilities complement and assist with MEYER's sub-rental and service customers. The following equipment is housed at these locations and can be shipped Nationwide to meet the needs of our customers in any location.

Rental Equipment:

Accumulators/ BOP Closing Units:

- 2 Station, 2 Bottle
- 3 Station, 2 Bottle
- 3 Station, 4 Bottle
- 4 Station, 4 Bottle
- 5 Station, 4 Bottle
- 5 Station, 6 Bottle
- 6 Station, 6 Bottle
- 6 Station, 8 Bottle
- 7 Station, 8 Bottle

Greasing Systems:

- High-Flow Grease Unit
- Standard Grease Unit
- 10 Station SPYDER[™] Manual Grease Manifold
- 15 Station SPYDER[™] Manual Grease Manifold
- Lincoln Pump/ Tube Assemblies

Test Units:

- Mobile Test Units
- Shop Test Units

<image>



6733 Leopard Street Corpus Christi, Texas 78409 Phone: 1-877-44-MEYER (63937) Fax: (361) 289-2138 Email: info@MeyerNow.com

MeyerNOW.com

MEYER SUB-RENTAL DIVISION



MEYER Sub-Rental Division

MEYER's rental facilities complement and assist with MEYER's sub-rental and service customers. The following equipment is housed at these locations and can be shipped Nationwide to meet the needs of our customers in any location.

Rental Equipment:

Frac Equipment:

- BOP's: 7-1/16" 5m
- Casing Elevators: 4-1/2" and 5-1/2"
- Drill Collars: 3-1/8" OD & 3-1/2" OD
- Drill Collar Handling Tools (Elevators, clamps and slips)
- DSA's ranging from 2-9/16" 5m through 13-5/" 10m
- Larkin Flanges: 7-5/8" and 8-5/8"
- Slip Type Elevators (MYT and YT)
- Spools ranging from 1-13/16" 10m through 11" 10m, Spacer Spool that range from 12" to 48" with sizes of 7-1/16", 5-1/8" and 4-1/16" and different pressure ratings.
- TIW Valves: 2-3/8" 8RD and 2-7/8" 8R
- Tubing Elevators: 2-3/8"NU, 2-3/8"EUE, 2-7/8"EUE and 3-1/2"EUE
- Various Crossover and Bit Subs
- Weco Flanges ranging from 2-1/16" 5m through 7"
 15m



- Frac Valves sizing from 2-1/6", 4-1/16", 5-1/8",
 7-1/16" 10m and 15m pressure ratings available.
- 5-1/8" 15K Horizontal Zipper Manifold
- Frac Heads with 4 or 6 ports ranging in sizes of 4-1/16", 5-1/8", 7-1/16" 10m and 15m pressure ratings available.
- Countless amount of blind flanges with a wide variety of sizes and pressure ratings.
- Assortment of 7-1/16", 5-1/8", 4-1/16" crosses that can be utilized for flow crosses on frac stacks.
- Diverse selection of adapter spools and DSA, sizes ranging from 2-1/16" 10m to 7-1/16" 15m.



6733 Leopard Street Corpus Christi, Texas 78409 Phone: 1-877-44-MEYER (63937) Fax: (361) 289-2138 Email: info@MeyerNow.com

MeyerNOW.com